SELEXEL

PRODUCT INFORMATION

SUPER HIGH SOLIDS METALLISED POLISH

A metallised polish for extreme strength and durability coupled with ease of removability. Non-yellowing cross linked polymer film. Does not discolour even the lightest floor. Produces a deep shine with excellent slip resistance. Responds brilliantly to all spray burnishing techniques.

Benefits: Slip Resistant Key Category : Specialised Application Type(s): Systemised

Specific Gravity: 1.04

pH 9

Pack = 5LX2 Gross Weight :10.94 kg Dimensions 185mm (w) x 279mm (d) x 286mm (h) Unit = 5L(BOT)Dimensions 185mm (w) x 134mm (d) x 283mm (h) Gross Weight: 5.47 kg

NEAT CHEMICAL INFORMATION



SELDEN Brand

Code A011

5L(BOT)

Stock ID A011-5LX2-SELDEN

HAZARD INFORMATION

Contains Benzisothiazolinone. May produce an allergic reaction. Safety data sheet available on request.

NOT HAZARDOUS

PERSONAL PROTECTION EQUIPMENT

NO MANDATORY PPE REQUIREMENT (for general chemical handling)

PRECAUTION PHRASES

RECOMMENDED TASKS FOR THIS PRODUCT

GORY TASK DESCRIPTION	DILUTON
FLOOR CARE POLISH	NEAT (100%)





NEAT CHEMICAL RISK / ECO IMPACT



(Environmental Impact Control) EIC

Above RcR and EIC are applicable for this chemical in its NEAT form. The IN USE values should be considered more 'significant'

CHECK FOR LATEST VERSION



This product has been audited and assessed as safe for a range of tasks. Use CleanFM to obtain task specific Chemical Safety Assessments www.cleanfm.com

> REACH compliant

SELDEN RESEARCH LIMITED & CLEANFM



This Task Card was produced by our innovative chemical and hygiene management system - CleanFM http://www.cleanfm.com for more information

Buxton, Derbyshire. SK17 9RZ t: 01298 26226 | f: 01298 26540 e: info@selden.co.uk

This product may be used for other tasks. You can perform REACH compliance audits for these on our Hygiene and Safety Management webiste - www.cleanfm.com