M015: SCREEN WASH

SUB-ZERO SCREENWASH

directions



SCREEN WASH	M015
sub-zero screenwash	

description De-ices windscreens. Cleans windscreens without smears. Prevents windscreen washers freezing in winter conditions.

Cleans windscreens without smears. Prevents freezing in winter conditions. Used by garages, motor pools, haulage application

contractors, minicabs, taxis, Public Authority Vehicles, buses etc.

For deicing: Use undiluted. Pour or spray onto area as required. Leave for about 5 minutes until the ice has liquefied then brush clear. Summer Use: Dilute 1 part product to 40 parts cold water and pour into washer tank. Winter Use: Dilute 1 part product to 10 parts cold water and pour into washer tank. Severe Winter Conditions: Dilute 1 part product to 1 part cold water and pour

into washer tank.

Technical		
	Composition	A blend of alcohol and surfactants
	Appearance	Clear liquid
	Colour	Blue
	Density	0.980
	рН	9.5 - 10.5
	Fragrance	Alcohol
	Stability	2 years in an unopened container
Biodegradability	All surfactants contained in Selden Products meet the requirements of the EU Detergent Directive 2005 – 2004/648/EC. This	

requires all surfactants to break down both quickly and completely into harmless material such as CO2 and water.

Product is for professional use only.

SELDEN RESEARCH LIMITED, STADEN BUSINESS PARK, BUXTON, DERBYSHIRE, SK17 9RZ T: 01298 26226 F: 01298 26540 E: SALES@SELDEN,CO,UK