

ACCELERATOR FREE SINGLE USE GLOVE, 100% NITRILE, POWDER FREE, 240MM LONG, 0.11MM THICK

High performance accelerator free nitrile single use glove for people sensitive to accelerators used in standard nitrile single use gloves.

FEATURES

- › High quality nitrile, soft and durable
- › Palm thickness 0.11mm (4.5 mil), weight: 5.4g size M
- › Accelerator free to avoid skin irritation to people sensitive to accelerators contained in standard nitrile single use gloves
- › Textured finish for improved grip and touch
- › Powder-free, latex free, non-sterile, AQL 1.5
- › Chlorinated inside to offer more comfort and reduce friction when donning
- › Antistatic properties due to inherent antistatic properties of nitrile



SUITABLE FOR

Typical Industries

- Aerospace
- Chemical
- Electronics
- Pharmaceutical
- Manufacturing
- Oil and Gas
- Repair and Finishing

Suitable Applications

- Chemical Handling
- Handling Oily Components
- Laboratory Analysis
- Light Assembly
- Paint Spraying

CERTIFICATION

CAT III	EN ISO 374-1:2016 + A1:2018 / Type B	EN ISO 374-5: 2016
0598	KPT	Virus

See overleaf for explanation

PRODUCTION INFORMATION		
MATERIALS	LINER:	Accelerator free nitrile
	COATING:	–
COLOUR	Green	
LENGTH (mm)	240	
CUFF STYLE	Beaded	

ORDERING DETAILS		
SIZE	CODE	PACKAGING
6/XS	SKG04525EB	100 singles per box
7/S	SKG04525ED	
8/M	SKG04525EF	
9/L	SKG04525EH	10 boxes per case
10/XL	SKG04525EJ	
11/XXL	SKG04525EL	

- ### RECOMMENDATIONS FOR USE
- **USE:** Single use glove. Not suitable for mechanical, thermal, heat, electrical, heavy chemical protection. Do not use near moving machines if there is a risk of entanglement
 - **STORAGE:** Store in dry conditions in the original packaging and away from direct sunlight
 - **CLEANING:** To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present
 - **LIFETIME:** Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

CERTIFICATION LEGENDS

PROTECTION AGAINST MICRO-ORGANISMS EN 374-5
VIRUS = Glove has passed ISO 16604:2004 (method B)

RESISTANCE TO CHEMICAL PERMEATION - EN ISO 374:2016

CODE	CHEMICAL	CODE	CHEMICAL	TYPE OF GLOVES	BREAKTHROUGH TIME
A	Methanol	J	n-Heptane	A	≥30 min for at least 6 chemicals
B	Acetone	K	Sodium hydroxide 40%		
C	Acetonitrile	L	Sulphuric acid 96%	B	≥30 min for at least 3 chemicals
D	Dichloromethane	M	65% Nitric acid		
E	Carbon Disulfide	N	99% Acetic acid	C	≥10 min for at least 1 chemical
F	Toluene	O	25% Ammonium hydroxide		
G	Diethylamine	P	30% Hydrogen peroxide		
H	Tetrahydrofurane	S	40% Hydrofluoric acid		
I	Ethyl acetate	T	37% Formaldehyde		

GLOBUS

EUROPE
www.globusgroup.com
E: sales@globus.co.uk
T: +44 (0)161 877 4747
F: +44 (0)161 877 4746

MIDDLE EAST & AFRICA
www.globusgroup.com/gcc
E: gcc@globusgroup.com
T: +971 4 882 9962
F: +971 4 882 9963

GLOBUS AMERICAS
www.globusgroup.com
E: americas@globusgroup.com

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM
 Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES
 Globus Americas LLC, 45 Rockefeller Plaza, Suite 2000, New York City, New York, 10111, USA

© 2023 Globus (Shetland) Ltd | SKY-DATA-TX4525-1123,1

EU Type-Examination Certificate issued by SATRA Technology Europe Limited, Bracetown Business Park, Clonee, D15YN2P, Republic of Ireland. (Notified Body No. 2777)

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.